

SURE-STOP® RUBBER (TPE)

WATERSTOP

DUMBBELL PROFILES

RUBBER THERMOPLASTIC ELASTOMERIC (TPE) GRADE

NEW RUBBER TECHNOLOGY:

- Heat Weldable for Joining - Fast, Simple & Strong
- Full Range of Intersections



PRODUCT DESCRIPTION


CORKJOINT Sure-Stop® Rubber (TPE) Waterstops lead the way in high technology waterstops and comply with international standards.

Sure-Stop® Rubber (TPE) Waterstops are extruded from a specially compounded rubber and are designed for use in water retaining and water excluding structures where a positive seal is required for poured in-situ concrete expansion, construction and contraction joints.

Sure-Stop® Rubber (TPE) Waterstops are designed for use in many types of applications and structures, and are available in a number of different size profiles to suit a project's requirement.

Sure-Stop® Rubber (TPE) Waterstops are available in rolls with separate intersections supplied to simplify and minimise on-site fabrication. The waterstop is heat weldable and allows for fast and easy on-site welding/joining.

The efficiency of any waterstop is very dependent on good workmanship, installation, and on full compaction of the surrounding concrete around the waterstop during concrete placement. Optimum performance will be achieved if the waterstop is installed by keeping these important factors in mind.



ADVANTAGES

- A full range of profiles and sizes to suit all types of construction requirements
- **Sure-Stop® Rubber (TPE) Waterstops** conform to, and exceed all major international standards
- High quality compounded Rubber (TPE) for long term durability and integrity
- Factory made intersections to simplify and minimise on-site fabrication
- On-site welding equipment is available upon request
- Ability to withstand high hydrostatic head pressures



AREAS OF APPLICATION

Water retaining structures:

- Water tanks
- Water treatment plants
- Sewage treatment plants
- Swimming pools
- Dams and spillways
- Reservoirs
- Bund walls

Water excluding structures:

- Basements
- Underground car parks
- Tunnels
- Retaining walls
- Suspended slabs
- Below ground slabs
- Roof & podium slabs

Note: The product's design and performance, its intended use, installation and final confirmation and approval for use, must be provided by the project's Design Engineer and Project Manager.




TYPICAL APPLICATIONS

EXPANSION JOINT

CONSTRUCTION JOINT

STANDARD DETAIL OF WALL APPLICATIONS



TECHNICAL FEATURES

COLOUR	Black
PACKAGING	Depending upon profile / requirement
ROLL WEIGHT	Dependent upon profile type
STORAGE CONDITIONS & SHELF LIFE	5 years from the date of production if stored properly in original, unopened and undamaged sealed packaging, in dry conditions out of direct sunlight at temperatures between +10°C and +40°C
MATERIAL TYPE	Rubber Thermoplastic Elastomeric (TPE)
WELDING TEMPERATURES	Approximately 190°C - 200°C
SERVICE TEMPERATURE RANGE	-25°C to +70°C



PHYSICAL PROPERTIES


PROPERTY	TEST METHOD	REQUIREMENT	RESULT
Tensile Strength	BS2782:320A	14.00 (minimum)	19
Elongation at Break, %	BS2782:320A	350 (minimum)	530
Specific Gravity	BS2782:620B	1.33 ± 0.03	1.349
Water Absorption at 23°C (%)	ISO 62	N/A	0.14
Hardness, Shore A	BS2782:365B	75 ± 5 Shore (BSS 45 ± 10)	73 Shore A (BSS 42)

Note: The above Physical Property test results have been obtained from an independent laboratory test report issued from Sirim QAS International dated 17/03/22, and a copy of the test report is available upon request from Corkjoint. Testing was conducted on test samples prepared from a specific batch of Sure-Stop Rubber (TPE) material properties can vary between batches.







FOR EXPANSION JOINTS




CJ 851




CJ 851-7




CJ 852



CJ 852-7




CJ 853




CJ 854


FOR CONSTRUCTION JOINTS




CJ 855



CJ 856



CJ 857



CJ 858

Note: Full dimension drawings available upon request



PROFILE WIDTH SELECTION


The width of waterstop depends upon the thickness of the concrete and positioning of the reinforcement. The thickness of the concrete should be greater than or equal to the width of the waterstop profile. Refer to your engineer for further clarification and approval.

SITE JOINING

CORKJOINT recommends the use of its specialised welding equipment for on-site welding which consists of thermostatically-controlled Welding Irons and special Welding Jigs (each type of **CORKJOINT Sure-Stop® Rubber (TPE) Waterstop** requires its own welding jig to suit the particular shape). On-site joining is a simple exercise using **CORKJOINT** Heat Welding Equipment comprising of an adjustable Welding Jig and Welding Iron. The ends of the waterstop are cut square and placed into the adjustable Welding Jig, then push the ends of the waterstop against the Welding Iron and bring the two ends together until the molten ends of the Rubber (TPE) fuse. When ordering Welding Equipment, please advise profile number of the waterstop

FACTORY MADE INTERSECTIONS

A wide range of standardised prefabricated intersection pieces are available allowing easy site welding of butt joints to **Sure-Stop® Rubber (TPE) Waterstop** junction pieces. Customised pieces can be made to suit. In such cases, drawings must be provided giving exact dimensions and jointing details.



WRITTEN SPECIFICATION

Where shown on the drawings waterstops shall be **Sure-Stop® Rubber (TPE) Waterstop** (state profile number required) as supplied by **CORKJOINT**. Provide factory made waterstop fabrications for all changes of direction, intersections and transitions, leaving only straight butt joined splices for on-site fabrication.

HEALTH AND SAFETY INFORMATION

Joining of **Sure-Stop® Rubber (TPE) Waterstop** is performed by heat welding which results in the discharge of hydrogen chloride mist and vapour. In confined spaces or in still air conditions, the use of a ventilation fan or suitable respirator should be used, and the advice and approval of the Site Safety Supervisor is essential. For further information or advice on health and safety precautions, safe handling, storage and correct disposal of products, please refer to the most recent product Safety Data Sheet (SDS), which is available upon request.



DISCLAIMER

The information and the recommendations relating to the application and end use of this product are given in good faith and are based on the information provided by the manufacturer of the product and/or the Company's current knowledge and experience in connection with the product when properly stored, handled and applied under normal conditions and no liability of final function at the job site is assumed. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability of, or fitness for, particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written and/or oral recommendations, or from any other advice offered by the Company. The Company also has no express or implied knowledge of any particular purpose for which the product is required and any such information given will not be taken into account in the supply of this product. No responsibility or liability by the Company will be accepted for misuse, misreading or derivation from recommended guidelines in respect of this product and the user shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith. The information contained in our brochure may change at any time without notice. Any use of this product, **Sure-Stop® Rubber (TPE) Waterstop**, in any application should be approved as suitable for use/application by the Design Engineer and Project Manager.

Effective Date: 02 February 2023

CORKJOINT (MALAYSIA) SDN BHD 383102-H

📍 No. 51, Jalan BRP 8/2, Bukit Rahman Putra Industrial Park, 47000 Sungai Buloh, Selangor, MALAYSIA

☎ +603 6148 8010

☎ +603 6148 8020

CORKJOINT (SINGAPORE) PTE LTD 200716724-K

📍 No. 10 Buroh Street #02-26 & 27, West Connect Building, SINGAPORE 627564

☎ +65 6455 9331

☎ +65 6455 8535

